


EMVA 1288 IMAGING PERFORMANCE

FLIR **BLACKFLY[®]S** **BFS-GE-50S5-BD**

Measurements are taken based on guidelines in the EMVA 1288 standard; the full definition can be found at EMVA.org. Camera settings are: maximum bit depth, 16-bit pixel format, and ISP disabled. The center wavelength is 525 nm unless otherwise noted. Results are captured at room temperature (20°C).

	Blackfly S BFS-GE-50S5M-BD	Blackfly S BFS-GE-50S5C-BD
Resolution	2448x2048	2448x2048
Sensor	Sony IMX264, CMOS, 2/3"	Sony IMX264, CMOS, 2/3"
Pixel Size	3.45	3.45
Firmware Version	2005.0.145.0	2005.0.145.0
ADC Bit Depth	12	12
Quantum Efficiency Mono (% at 525 nm)	65.55	N/A
Quantum Efficiency Blue (% at 470 nm)	N/A	49.87
Quantum Efficiency Green (% at 525 nm)	N/A	60.65
Quantum Efficiency Red (% at 630 nm)	N/A	46.50
Temporal Dark Noise (Read Noise) (e-)	2.27	2.37
Temporal Dark Noise (Read Noise) (DN)	13.28	13.39
Signal to Noise Ratio Maximum (dB)	40.35	40.58
Signal to Noise Ratio Maximum (Bits)	6.70	6.74
Absolute Sensitivity Threshold (γ)	4.22	4.72
Absolute Sensitivity Threshold (e-)	2.77	2.87
Saturation Capacity (Well Depth) (e-)	10849	11440
Saturation Capacity (Well Depth) (γ)	16550	18836
Dynamic Range (dB)	71.87	72.02
Dynamic Range (Bits)	11.94	11.96
Gain (e-/ADU)	0.17	0.18

Blackfly S BFS-GE-50S5M-BD Spectral Response Curve



Blackfly S BFS-GE-50S5C-BD Spectral Response Curve

