

EMVA 1288 IMAGING PERFORMANCE


FLIR BLACKFLY[®]S

BFS-U3-122S6-BD

Measurements are taken based on guidelines in the EMVA 1288 standard; the full definition can be found at EMVA.org. Camera settings are: maximum bit depth, 16-bit pixel format, and ISP disabled. The center wavelength is 525 nm unless otherwise noted. Results are captured at room temperature (20°C). Using FLIR test software version 4.1.

	BFS-U3-122S6M-BD	BFS-U3-122S6C-BD
Resolution	4096 x 3000	4096 x 3000
Sensor	Sony IMX304, CMOS, 1.1"	Sony IMX304, CMOS, 1.1"
Pixel Size (µm)	3.45	3.45
Firmware	1906.0.157.0	1906.0.157.0
ADC	12-bit	12-bit
Quantum Efficiency Mono (% at 530 nm)	67	N/A
Quantum Efficiency Blue (% at 460 nm)	N/A	48
Quantum Efficiency Green (% at 530 nm)	N/A	59
Quantum Efficiency Red (% at 625 nm)	N/A	47
Temporal Dark Noise (Read Noise) (e-)	2.34	2.36
Temporal Dark Noise (Read Noise) (DN)	13.74	13.92
Signal to Noise Ratio Maximum (dB)	40.33	40.35
Signal to Noise Ratio Maximum (Bits)	6.70	6.70
Absolute Sensitivity Threshold (γ)	4.26	4.83
Absolute Sensitivity Threshold (e-)	2.84	2.86
Saturation Capacity (Well Depth) (e-)	10789	10850
Saturation Capacity (Well Depth) (γ)	16185	18308
Dynamic Range (dB)	71.60	71.57
Dynamic Range (Bits)	11.89	11.89
Gain (e-/ADU)	0.17	0.17

BFS-U3-122S6M-BD



BFS-U3-122S6C-BD

