



| | | | | |
|---------------------------|------------|-------------------------|------------|--------------------|
| 4/3" 2.8/8.5mm C | | 4/3" | 1" | 2/3" |
| FOCAL LENGTH | | f=8.5mm | | |
| MAX. DIAMETER (RATIO) | | F=1:2.8~22 | | |
| ELEMENT | | 14 GROUPS 17 ELEMENTS | | |
| PICTURE SIZE | | 13.8x18.4mm | 9.6x12.8mm | 6.6x8.8mm |
| ANGLE | VER. ANGLE | 77.1° | 57.9° | 41.6° |
| | HOR. ANGLE | 93.5° | 72.9° | 53.8° |
| | DIA. ANGLE | 106.0° | 85.5° | 64.8° |
| DISTORTION (TV) | | 0.12% (WD=300mm) | | |
| SHOOTING RANGE AT | VER. | 179.1mm | 124.9mm | 85.9mm |
| | HOR. | 238.4mm | 166.4mm | 114.5mm |
| MINIMUM FOCUS | DIA. | 297.3mm | 207.9mm | 143.1mm |
| | DIA. | 297.3mm | 207.9mm | 143.1mm |
| MINIMUM FOCUS DISTANCE | | 0.1m | | |
| FLANGE BACK | | 17.526mm in air | | |
| BACK FOCUS | | 12.9mm in air | | |
| FILTER SCREW SIZE | | M72x075 | | |
| FRONT/REAR EFFECTIVE DIA. | | FRONT ϕ 45.5mm | | REAR ϕ 16.5mm |
| MOUNT | | C-MOUNT | | |
| EXIT PUPIL | | -75.2mm | | |
| TEMPERATURE RANGE | | -10~+50°C | | |
| STORAGE TEMPERATURE RANGE | | -20~+60°C | | |
| RESOLUTION CENTER/CORNER | | CENTER 160本/mm | | CORNER 63本/mm |
| LENS COATING | | WIDE BAND MULTI COATING | | |
| WEIGHT | | 245g | | |

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。



| | | | | | |
|------------|-------|-----|-------------------|------|--------|
| | | 尺度 | 1/1 | 工場番号 | FR1089 |
| | | 機種名 | 4/3" F2.8 f=8.5mm | | |
| 2014.12.25 | 更新 | 機種番 | LM8XC 外観図 | | |
| 2013.4.15 | 作成年月日 | | | | |